



SOT23-3
Low dropout linear regulator in a SOT23-3 Plastic Package.

24V 1.5μA ±2%

Low power consumption,Low voltage drop,Small temperature drift coefficient,High input voltage up to 24V,The static current 1.5μA,The output voltage accuracy:±2%,HF Product.


For use in power equipment,Communication equipment,Audio and video equipment.




1	GND		3	VIN	
2	VOUT				

See Marking Instructions.


/ Basic Application




/ High Output Current Voltage Regulator




/ Short-Circuit Protection




/ Circuit for Increasing Output Voltage




/ Constant Current Regulator




/ Double Output Circuit





2026




7533M

Note:

7533M: Product Type Code

****: Lot No. Code, code change with Lot No

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT23-3	3,000	10	30,000	4	120,000	7" ×8	210×205×205	445×435×230