

/ Descriptions

SOT-323

PNP

Silicon PNP Digital Transistor in a SOT-323 Plastic Package.


/ Features

With built-in bias resistors, simplify circuit design, reduce a quantity of parts and manufacturing process.


/ Applications

Switching, Inverter circuit, Interface circuit and driver circuit applications.

/ Equivalent Circuit



/ Pinning



PIN1 Emitter

PIN 2 Base

PIN 3 Collector

/ Marking

Marking	H16
---------	-----


/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Output Voltage	V_{CC}	-50	V
Input Voltage	V_{IN}	-40	V
		10	V
Output Current	I_C	-100	mA
	I_O	-30	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55~150	

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Input Voltage	$V_{I(off)}$	$V_{CC}=-5.0V$ $I_O=-100\mu A$			-0.5	V
	$V_{I(on)}$	$V_O=-0.3V$ $I_O=-2.0mA$	-3.0			V
Output Voltage	$V_{O(on)}$	$I_O=-10mA$ $I_i=-0.5mA$		-0.1	-0.3	V
Input Current	I_i	$V_i=-5.0V$			-0.18	mA
Output Cut-off Current	$I_{O(off)}$	$V_{CC}=-50V$ $V_i=0V$			-0.5	μA
DC Current Gain	G_i	$V_O=-5.0V$ $I_O=-5.0mA$	68			
Transition Frequency	f_T	$V_{CE}=-10V$ $I_E=5.0mA$ $f=100MHz$		250		MHz
Resistance1	R_1		32.9	47	61.1	K Ω
Resistance Ratio	R_2/R_1		0.8	1.0	1.2	


/ Electrical Characteristic Curve




/ Package Dimensions

SOT-323

单位: mm



/ Marking Instructions



H


16

Note:

H Company Code

16 Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5

10±1 sec.

Temp:260±5

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7" x8	180×120×180	390×385×205

/ Notices